

# Heated Holding Cabinets

MP-941  
Single Drawer

MP-942  
Two Drawer

MP-943  
Three Drawer

MP-944  
Four Drawer



*Heated Holding Cabinets keep foods hot and tasty for long periods of time before serving. The right holding cabinet can make the difference between what you sell and what you throw away.*

## Description

Space-saving single and multi-drawer heated holding cabinets designed to hold different foods within proper temperature ranges conveniently at hand prior to serving.

## Configuration

The MP-941 is a single drawer, modular unit that can be placed on countertops, side by side or stacked, or mounted under countertops. Multi-drawer units allow separate side-by-side holding environments that can be programmed with independent temperatures for each drawer. Rear panel outlets allow multiple single drawer units to be conveniently powered from one electrical source.

- Single and three-drawer units have rear-mounted power cords.
- Two and four drawer units have side-mounted power cords.

- Choice of right or left side controls on two, three and four drawer units.
- Right side only controls on single drawer unit.
- Fully insulated cabinet with high temperature drawer gasket.
- Positive drawer closure.
- Low friction bearings.
- Adjustable leveling feet (not available on MP-944.)

## Main Features

- Electronic temperature control with four-digit display in °F or °C.
- Built-in digital clock.
- Programmable temperature input with program lock to prevent accidental changes in settings.
- Choice of right or left-side control panel (MP-941 right side only.)
- Energy efficient operation.
- Slide vent humidity control, each drawer.
- Single-piece welded drawer and liner.
- Accepts standard steam table pans.

## Henny Penny Corporation

P.O. Box 60  
Eaton, OH 45320

+1 937 456.8400  
+1 937 456.8402 Fax

## Toll free in USA



**800 417.8417**  
**800 417.8402 Fax**

[www.hennypenny.com](http://www.hennypenny.com)



# MP-941 MP-942 MP-943 MP-944 Specifications

## Dimensions



### MP-941





### MP-942



### MP-943



### MP-944



## Clearances

Control Side: MP-942, MP-944 add 2 in. (51 mm) for side power cord.  
Back: MP-941, MP-943 add 2 in. (51 mm) for rear power cord.

## Capacity

One standard steam table pan 12 x 20 x 4 in. (305 x 508 x 102 mm) per drawer.

## Heating

140-210°F (60-99°C)

## Shipping Weight

<b>MP-941</b> 67 lbs. (30 kg)	<b>MP-942</b> 139 lbs. (63 kg)	<b>MP-943</b> 200 lbs. (91 kg)	<b>MP-944</b> 278 lbs. (126 kg)
----------------------------------	-----------------------------------	-----------------------------------	------------------------------------

## Listings

UL, UL Sanitation, CUL, CE

## Electrical

Model	Voltage	Phase	Cycle/Hz	KW
<b>MP-941</b>	120	1	50/60	.475*
	230	1	50	.475*
<b>MP-942</b>	120	1	50/60	.95
	230	1	50	.95
<b>MP-943</b>	120	1	50/60	1.4
	230	1	50	1.4
<b>MP-944</b>	120	1	50/60	1.9
	230	1	50	1.9

\*KW are 1.4 with rear electrical outlet added for connecting additional units.

Specifications subject to change without notice

All international voltages available

## Order from:

Manufactured by:

**Henny Penny Corporation**  
P.O. Box 60  
Eaton, OH 45320